

**RONDA normtech**

- 6203.B

**RONDA mastertech**

- 7003.L

- 7003.N


- 7004.N

- 7004.P

WWW.COVERWATCHES.COM

You have decided to buy a watch, which was assembled by a watchmaker using a Ronda movement. Please note that no watches are produced or distributed under the Ronda brand.

In case of repairs, guarantee claims and questions concerning the functioning of a watch, purchasers and consumers should contact their retailer or the watch manufacturer, for which the relevant information can be found in the sales or guarantee documentation provided with the watch.



Cal. 6203.B

**Crown A**

**Pos. I Position of rest** (watch running)

**Pos. II Quick-change correction for date**

*The date can also be corrected during the day-changing phase between 10.00 pm and midnight. The date of the following day has to be set, because no automatic date change takes place at midnight.*

- Pull the crown out to position II (watch still running).
- Turn the crown clockwise until the required date appears.
- Push the crown back into position I.

**Pos. III Setting the time** (both time zones together)

- Pull the crown out to position III (watch stopped).
- Turn the crown, until the current time is displayed (remember the 24-hour cycle).
- Push the crown back into position I.

Cal. 6203.B

**Crown B**

**Pos. I Position of rest**


**Pos. II Setting the time of the 2<sup>nd</sup> time zone**

*During the time setting of the 2<sup>nd</sup> time zone, crown A must be in position I.*

- Pull the crown out to position II.
- Turn the crown, until the desired time is displayed.
- Push the crown back into position I.

Cal. 7003.L

Cal. 7003.N



Cal. 7004.N

Cal. 7004.P

**Pos. I Position of rest** (watch running)

**Pos. II Quick-change correction for date**

*The date can also be changed during the day-changing phase between approx. 8.00 pm and midnight. The date of the following day has to be set, because no automatic date change takes place at midnight.*

- Pull the crown out to position II (watch still running).
- Turn the crown until the current date appears.
- Push the crown back into position I.

Cal. 7003.L / 7003.N / 7004.N / 7004.P

**Pos. III Setting the time**

- Pull the crown out to position III (watch stopped).
- Turn the crown, until the current time is displayed (remember the 24-hour cycle).
- Push the crown back into position I.

**Setting the day of the week**

*There is no quick-change correction available for setting the day of the week.*

- Pull the crown out to position III (watch stopped).
- Turn the hands forward by turning the crown, until the current day of the week appears.
- Push the crown back into position II and set the current date using the quick change correction.
- Push the crown back into position I.

**Cal. 6203.B**

Battery type: 373/SR916SW (Ø 9.5 mm x 1.6 mm)

**Cal. 7003.L / 7003.N / 7004.N / 7004.P**

Battery type: CR 2016 (Ø 20 mm x 1.6 mm)

Precision: +20/-10 seconds per month

